

# Bollards: Promenade - 8" Round

BL-PRO SERIES

## SPECIFICATIONS

- Decorative round die-cast housing made from corrosive resistant aluminum.
- Post base is constructed from extruded aluminum tubing.
- Concealed—low glare lens diffuser (acrylic) with low glare up-light cone (polycarbonate).
- All external fasteners are made of stainless steel.
- Weatherproof and durable silicone gaskets.
- Lamp included with the fixture.
- DMX 512 Interface (for RGB LED model).
- UV stabilized, textured charcoal gray polyester powder coat finish.
- IP54 rated conforms to IEC rating with 3 joules shock resistant.



BL - PRO

## ORDERING GUIDE

MODEL NUMBER		LIGHT SOURCE OPTIONS						OPTIONS / ACCESSORIES	
PRODUCT FAMILY	BOLLARD STYLE	OPTICS	LAMP WATTAGE	LAMP TYPE/BASE	VOLTAGE	BALLAST TYPE	OPTION-1	OPTION-2	
Basic Model									
BL	- PRO								
BL = BOLLARD	PRO = Promenade 10" Round	1 = Diffuse White Top uplite 2R = with Red uplite 2B = with Blue uplite 2C = with Green uplite 2Y = with Yellow uplite 2R=RGB LED	50 = 50W 70 = 70W/75W 60 = RGB LED 26 = 26W PLT 32 = 32W PLT 42 = 42W PLT	MME = MH-MEDIUM BASE HME = HPS MEDIUM BASE PS = PULSE START MH CF = COMPACT TRIPLE TUBE XX = LED	120 = 120V 208 = 208V 240 = 240V 277 = 277V MT = MULTI VOLTAGE XXX - LED 120V	C = CWA HX = High Reactance	SIF = SINGLE IN-LINE FUSE DIF = DOUBLE IN-LINE FUSE FINISHES: GR = GRAY BZ = BRONZE WT = WHITE CH = CHARCOAL GRAY (STD)		