

Speaker Disconnect Unit for Pole Mounting


System load capacity of 200 lbs.

Disconnect unit with 2 electrical contacts-standard.

Case grounded.



Frontal View of Speaker



Pole Ordered Separately

UL & CUL Listed
277/240/208 V. 15 AMP
& 120 V. 20 AMP AC per contact.

Minimum Load: 20 lbs.

Standard Finish: Natural Aluminum

Consult factory for other finishes

- Pole Top Connection Box
- Adapter
- Pole Mounted Fitter
- U-Bolt Clamps
- Disconnect Unit Fitter
- Position Aligned Non-Rotating Divided Pipe Arm
- Electrical Supply Wires
- Raising and Lowering cable
- Interlocking Alignment Pins
- Fixed Disconnect Assembly
 - Knife Contacts
 - 3-Way Tracking Guide and Support
 - Disconnect Unit Cover
- Lower Disconnect Assembly
 - Precision Cast Stainless Steel Guide Post
 - Precision Cast Stainless Steel Support Arms
 - Spring Contacts

OPTIONS	SUFFIX
(3) Contacts	3C
(4) Contacts	4C
Add-On Weights	CW
Stainless Steel Cover	HD
Bronze Painted	BRZ
Silver Painted	SLV
Black Painted	BLK

EPA: 1.13 Sq. Ft. per arm assy. (less speaker) Weight: 32 lbs. (less speaker)

WARNING: Not for lifting people or raising/lowering over people.

Specifications subject to change without notice.

ACCESSPOINT Lowering Systems Inc.

www.access-point.ca • 905-648-1013 • tbreakey@access-point.ca